

nervous system depression and dermatitis.

CARCINOGENICITY: NTP CARCINOGEN: No IARC MONOGRAPHS: Yes OSHA REGULATED: No
This material contains styrene, which is classified as a possible carcinogen for humans (2B) by IARC. This material contains ethylbenzene which is classified as "possibly carcinogenic to humans" (2B) by IARC.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

Pre-existing eye, skin and respiratory disorders may be aggravated.

EMERGENCY AND FIRST AID PROCEDURES

INHALATION: REMOVE TO FRESH AIR. APPLY ARTIFICIAL RESPIRATION IF NECESSARY.
SPLASH(EYES): FLUSH EYES IMMEDIATELY WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. SPLASH(SKIN): WASH AFFECTED AREAS THOROUGHLY WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING AND WASH THOROUGHLY BEFORE REUSE. FOR SEVERAL EXPOSURES GET UNDER SAFETY SHOWER AFTER REMOVING CLOTHING, THEN GET MEDICAL ATTENTION. INGESTION: DO NOT INDUCE VOMITING. GIVE 1 TO 2 CUPS OF MILK OR WATER TO DRINK. DO NOT GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS OR CONVULSING PERSON. CONSULT PHYSICIAN IMMEDIATELY.

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

ELIMINATE ALL SOURCES OF IGNITION. ABSORB WITH INERT MATERIAL (SAND, VERMICULITE, ETC.), SWEEP OR SCOOP UP AND PUT IN DISPOSAL CONTAINER. FLUSH AREA OF SPILL WITH WATER.

WASTE DISPOSAL METHOD

Waste must be disposed of in accordance with federal, state and local environmental control regulations. Incineration is the preferred method. Empty containers must be handled with care due to product residue and flammable solvent vapor. Decontaminate containers prior to disposal. DO NOT HEAT OR CUT EMPTY CONTAINER WITH ELECTRIC OR GAS TORCH.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Keep away from heat, sparks and open flame. Ground containers during storage and transfer operations. Store in tightly closed containers to prevent moisture contamination. Do not reseal if contamination is suspected. Avoid contact with skin and eyes.

OTHER PRECAUTIONS

Do not take internally. Avoid prolonged contact. Ground equipment to prevent accumulation of static charge.

===== SECTION VIII - CONTROL MEASURES =====

RESPIRATORY PROTECTION

Use self-contained breathing apparatus where vapor concentration may be above TLV limits. Below TLV limits, use a combination vapor and particulate respirator for spray application or a vapor respirator for non-spray applications.

VENTILATION

Exhaust ventilation sufficient to keep the airborne concentration of the

solvents, HDI and polyisocyanate below their respective TLV must be utilized.

PROTECTIVE GLOVES

Chemical resistant gloves: Cover as much of the skin area as possible with appropriate clothing.

EYE PROTECTION

Safety glasses, splash goggles or face shield. Contact lenses should not be worn.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

Safety showers and eyewash stations should be provided.

WORK/HYGIENIC PRACTICES

Wash hands thoroughly before eating or using the washroom. Smoke in smoking areas only.

===== SECTION IX - TRANSPORT INFORMATION =====

DOT (GROUND)

1.3 gallons (5 liters) or less:
UN1263,Paint,3,PGIII, "Ltd. Qty."

Greater than 1.3 gallons (5 liters):
UN1263, Paint,3,PGIII

AIR

UN1263,Paint,3,PGIII

===== SECTION X - REGULATORY INFORMATION =====

CALIFORNIA PROPOSITION 65

This product contains a chemical known to the State of California to cause cancer.

Contains: Ethylbenzene -

===== SECTION XI - DISCLAIMER =====

The information contained herein is based on the data available to us and is believed to be correct. However, ELLIS PAINT CO. makes no warranty expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. ELLIS PAINT CO. assumes no responsibility for injury from the use of the product described herein.