

Universal Liquid Flatting Agent

Universal Liquid Flatting Agent 32A is used to reduce the gloss level of Solvent Based products to Semi-Gloss, Satin or Flat.

Product is available in round metal quarts, six cans per case.

Universal Liquid Flatting Agent 32A is formulated at VOC level of 100 grams per liter. It will not increase the VOC level of products formulated at 100 grams per liter.

To reduce the gloss of solvent based products from full gloss to semi-gloss, satin or flat, follow the instructions for your desired gloss level:

DIRECTIONS FOR USE

Semi-Gloss* (45° - 55°)

In a separate and larger container, under continuous stirring, gradually add 50 oz. of 32A Universal Liquid Flatting Agent to one gallon of solvent based paint. Stir thoroughly 4-5 minutes, preferably with a mechanical mixer or under shaker to achieve smooth finish.

Satin* (25° - 35°)

In a separate and larger container, under continuous stirring, gradually add 60 oz. of 32A Universal Liquid Flatting Agent to one gallon of solvent based paint. Stir thoroughly 4-5 minutes, preferably with a mechanical mixer or under shaker to achieve smooth finish.

Flat* (8° - 10°)

In a separate and larger container, under continuous stirring, gradually add 70 oz. of 32A Universal Liquid Flatting Agent to one gallon of solvent based paint. Stir thoroughly 4-5 minutes, preferably with a mechanical mixer or under shaker to achieve smooth finish.

* IMPORTANT NOTE:

- Gloss levels as tested using Ellis 4400 BASE SERIES
- Gloss levels may vary when other than Ellis products are used.

