

MAXIMUS WATERBORNE UNIVERSAL FLOW AGENT

Description:

Maximus Waterborne 7999 Universal Flow Agent is an additive for the Maximus Waterborne Enamel 7900 Series, in addition to waterborne industrial enamels. When added to Maximus 7900 Series, or waterborne industrial enamel, Maximus 7999 Universal Flow Agent provides improved workability and flow of the coating.

Partial List of Uses:

- Add to waterborne industrial enamels to reduce viscosity
- Improves workability of coating

Benefits:

- Improves performance and workability of industrial waterborne enamels



TECHNICAL DATA

Product Number:	7999 Universal Flow Agent
Colors:	Milky White Liquid
Viscosity:	14 seconds, #2 Zahn Cup @ 77°F
Solids by Weight:	21.71
Solids by Volume:	20.44
V.O.C. (Volatile Organic Compounds): *	Less than 100 grams per liter (0.8 lbs/gal)
Solvent(s) Used:	Glycol Ether
Finish:	N/A
Flash Point:	>200°F/TCC
Dry-To-Touch @ 77°F:	N/A
Dry-To-Handle @ 77°F:	N/A
Recoat time @ 77°F:	N/A
Coverage (Theoretical):	328 square feet per gallon @ 1mil DFT

MAXIMUS WATERBORNE UNIVERSAL FLOW AGENT

MAXIMUS WATERBORNE - UNIVERSAL FLOW AGENT:

Add to waterborne industrial coatings for increased performance and workability.

DIRECTIONS FOR USE: MAXIMUS WATERBORNE UNIVERSAL FLOW AGENT may be added to up to 20% by volume to improve the workability and flow of waterborne industrial coatings. Do not overthin; sagging may result.

IMPORTANT! When MAXIMUS WATERBORNE UNIVERSAL FLOW AGENT is mixed with waterborne industrial coatings, the mixture will have the hazards of both components. Observe all applicable precautions. Beware opening the packages, READ ALL WARNING LABELS. FOLLOW ALL PRECAUTIONS.

MIXING: Mix thoroughly before use and/or after thinning.

CLEAN-UP: Clean pad applicators, brushes and rollers immediately after use with soap and cold water. Clean spray equipment immediately after use with water followed with Ellis 80/20 Zero VOC Exempt Solvent.

SHELF LIFE: Shelf life is 1 year from date of manufacture when stored at temperatures not to exceed 90°F.

Refer to product label and Material Safety Data Sheet (MSDS) for cautions and warnings pertaining to this product.

Limited Warranty:

Ellis Paint Company certifies that all Ellis coatings delivered to the customer in new, sealed containers will meet all pertinent quality standards presented in Ellis published literature. Since matters of surface preparation, application procedures and other local factors which affect performance are beyond its control, Ellis assumes no liability for coating failure other than to supply replacement material for Ellis coatings shown to be defective. If you have questions, contact your dealer, visit www.ellispaint.com, or call Ellis Paint Company. There is no other warranty, either expressed or implied.

